





More Info

Data sheet

## acs 1100 d3 - gantry - 2x varithek<sup>®</sup>

The mobile front cooking station with innovative extraction technology.

The mobile station with integrated "air cleaning system" edge extraction technology on three sides, made entirely of high-quality stainless steel, offers unlimited flexibility and mobility when cooking and makes front cooking an experience – without any unwanted odours.

With a digital control and a reliable, multi-layer filter system in the substructure consisting of a grease, activated carbon and pollutant filter, neutralising all odours. Thanks to the perfectly designed air circulation with edge extraction on 3 sides (d3), a flame-retardant high-performance cyclone filter is used to remove the vapours formed during cooking from the grease, water and odour-laden air right where they originate. The digital control offers a variety of useful functions, such as a display indicating the degree of wear of the filter elements (activated carbon filter), 4-level extraction power as well as a display of faults by means of continuous text. Different coloured LED lights indicate the operating status, an operating hours counter is also integrated and there is a safe alarm function with a buzzer.

+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS acs 1100 d3 - gantry - 2x varithek®







## TECHNICAL SPECIFICATIONS

Order number	91 14 04 02
Ambient temperature	+5°C to +40°C
Wheel diameter	80 mm
Castor	4 swivel castors with brakes
Protection class	IPX4
Cable length	2.000 mm
Plug type	CEE-Plug 400V/16A
Rated voltage	3N AC 400 V 50/60 Hz
Connected load	11.000 W
Weight	145 kg
Material	stainless steel 1.4301 (CNS)
Dimensions	1100 x 722 x 1300 mm

## BENEFITS

3-sided stainless steel panelling, rustproof, hygienic, brushed matt finish and securely welded.

Optimal hygiene with the 3-sided germ guard gantry, fixed laminated safety glass and more efficient extraction through side splash guard panels.

Elimination of odours and bacteria/microorganisms.

Safe to move with 4 swivel castors and locking brakes, DIN 18867, Part 8.

2 moisture-proof sockets with a hinged cover for cooking modules on the left and right.

Side walls, splash guard, filter, fan and collection components, inspection flap and seal can be removed without tools.

High-performance grease separator and collection trays are dishwasher-safe.