



More Info



Data sheet

thermoport® CNS 1600-D circ.heated

The heated food transport trolley with a serving option.

The mobile frontloader with heatable, precise and powerful circulating air heating (digitally controllable) is used for the safe transport of food in a GN system and for keeping the food hot, with an additional serving option on top. The mobile kitchen for the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid for low-temperature cooking. Additional cooling option is possible with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

thermoport® CNS 1600-D circ.heated



TECHNICAL SPECIFICATIONS

Dimensions	492 x 769 x 963 mm
Material	stainless steel 1.4301 (CNS)
Weight	40,4 kg
Connected load	763 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	1.500 mm
Heating Area	max. +95°C
Capacity with GN	78 L
Protection class	IPX5
Hygienic design	H2
Support rails	16
Rail distance	37 mm
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm
Max. loading capacity	150 kg
Ambient temperature	-20°C to +100°C
GN-Norm	GN 1/1

Order number

85 01 09 03

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior tightly welded with seamlessly deep-drawn support rails in hygienic design H2.

Lid with a moulded stacking recess and all-round seal suitable for use with foodstuffs.

Double-walled insulation, low loss of heat/cold.

Uniform heat distribution, even when fully loaded.

Steam slider for moisture regulation.

Mobile with robust, fixable castors and a push handle.

Corner bumpers and a lid seal for impact protection.

Non-slip loading on the lid with a moulded stacking recess.

Suitable for outdoor use, splash-proof (IPX4).

Removable door seal/heating system, quick and easy cleaning.

High-pressure cleaner can be used on the interior without the heating system, splash-proof (IPX5).